

# AC150 Series

Low Cost, Multipurpose Accelerometer, Top Exit 2 Pin Connector,  
100 mV/g, ±15%



VIBRATION ANALYSIS HARDWARE



## Product Features


Low Cost Accelerometer - Perfect for Permanent Mounting

Excellent Choice for Budget Conscious Data Collection

- ▶ ± 80 g, peak Dynamic Range
- ▶ 1-10000 Hz (60-600,000 CPM) Frequency Response
- ▶ Standard 2 Pin MIL Connection or Integral Cable

### AC150-1A 2 Pin Connector


Connector Pin	Polarity
A	(+) Signal/Power
B	(-) Common



Stock Product

### AC150-2C CB103 Integral Cable


Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire



Built To Order

### AC150-3C CB206 Armored Integral Cable


Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire



Built To Order

### AC150-6C CB611 Heavy Duty Armored Integral Cable

Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire



Built To Order

Specifications	Standard	Metric
Part Number	AC150	M/ or M8/AC150
Sensitivity (±15%)	100 mV/g	
Frequency Response (±3dB)	60-600,000 CPM	1,0-10000 Hz
Dynamic Range	± 80 g, peak *V <sub>source</sub> ≥ 22V, 12Vbias	
<b>Electrical</b>		
Settling Time	<2.5 seconds	
Voltage Source (IEPE)	18-30 VDC	
Constant Current Excitation	2-10 mA	
Spectral Noise @ 10 Hz	14 µg/√Hz	
Spectral Noise @ 100 Hz	2.3 µg/√Hz	
Spectral Noise @ 1000 Hz	2 µg/√Hz	
Output Impedance	<100 ohm	
Bias Output Voltage	10-14 VDC	
Case Isolation	>10 <sup>8</sup> ohm	

Specifications	Standard	Metric
<b>Environmental</b>		
Operating Temperature Range	-58 to 250 °F	-50 to 121 °C
Maximum Shock Protection	5,000 g, peak	
Electromagnetic Sensitivity	CE	
Sealing	Welded, Hermetic	
Submersible Depth	200 ft.	60 m
SIL Rating	SIL 2	
<b>Physical</b>		
Sensing Element	PZT Ceramic	
Sensing Structure	Shear Mode	
Weight	3.2 oz	90 grams
Case Material	316L Stainless Steel	
Mounting Thread	1/4-28 Blind Tapped Hole	
Connector (Non-Integral)	2 Pin MIL-C-5015	