

# AC915 Series

Low Capacitance, Intrinsically Safe Accelerometer, Top Exit 2 Pin Connector, 100 mV/g, ±10%



VIBRATION ANALYSIS HARDWARE



II 1 G D



## Regulatory Information

Ex ia IIC T3/T4  
 CLI Groups A, B, C, D  
 CLII Groups F, G  
 CLIII

CSA 22 UKEX 1408X  
 Ex ia IIC T3/T4 Ga  
 Ex ia I Ma  
 Sira 15 ATEX 2152X


Operating Temperature Code: T4 Ex ia IIC T3/T4 Ga  
 Ambient Temperature Range = -40 to 80°C  
 Ex ia I Ma

Operating Temperature Code: T3 IECEX SIR 15.0060X  
 Ambient Temperature Range = -40 to 125°C  
 Ex ia IIC T3/T4 Ga  
 Ex ia I Ma

Ui = 28 Vdc li = 100 mA  
 CSA 221421

### AC915-1A 2 Pin Connector


Connector Pin	Polarity
A	(+) Signal/Power
B	(-) Common



Stock Product

### AC915-2C CB193 Integral Cable


Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire



Built To Order

### AC915-3C CB296 Armored Integral Cable

Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire



Built To Order

Specifications	Standard	Metric	Specifications	Standard	Metric
Part Number	AC915	M/ or M8/AC915	<b>Environmental</b>		
Sensitivity (±10%)	100 mV/g		Operating Temperature Range	-40 to 250 °F	-40 to 121 °C
Frequency Response (±3dB)	30-900,000 CPM	0.5-15000 Hz	Maximum Shock Protection	5,000 g, peak	
Frequency Response (±10%)	60-600,000 CPM	1.0-10000 Hz	Electromagnetic Sensitivity	CE	
Dynamic Range	± 80 g, peak		Sealing	Welded, Hermetic	
<b>Electrical</b>			Submersible Depth	200 ft.	61 m
Settling Time	<3 Seconds		<b>Physical</b>		
Voltage Source (IEPE)	18-28 VDC		Sensing Element	PZT Ceramic	
Constant Current Excitation	2-4 mA		Sensing Structure	Shear Mode	
Spectral Noise @ 10 Hz	6.5 µg/√Hz		Weight	3.2 oz	90 grams
Spectral Noise @ 100 Hz	2 µg/√Hz		Case Material	316L Stainless Steel	
Spectral Noise @ 1000 Hz	1.8 µg/√Hz			0.83 in (21 mm)	Diameter
Output Impedance	<100 ohm				Mounting
Bias Output Voltage	10-14 VDC				