

Portable digital Pressure gauge Model CPG2300

WIKA data sheet CPG2300



Applications

- Portable Field Calibration
- Calibration Labs
- Semiconductor Manufacturers
- Utilities
- Pharmaceutical / Medical / Health Care

Special features

- Ranges to 6000 psi
- Absolute, gauge, bi-directional or vacuum
- Accuracy: 0.015%FS
- Dual sensor
- Dynamic Temperature Compensation from 0-50°C
- Two year warranty



Portable digital pressure gauge, model CPG2300

Description

Applications

The CPG2300 Portable Digital Pressure Gauge is used in diverse applications from rugged field calibration of pressure transmitters used in gas transmission, to testing and calibration of transducers in clean rooms and nuclear power plants. Wherever there is a need for a high level of accuracy in a handheld pressure calibration device.

Functional Flexibility

The CPG2300 Portable Digital Pressure Gauge has one of the best uncertainty specifications of any portable pressure calibration instrument. With an uncertainty of 0.015% FS, technicians are able to achieve the test uncertainty ratios required for modern transmitters. Temperature compensation from 0 to 50°C, permits use in most environments, without degradation of accuracy. Seventeen selectable pressure units and one user defined unit allows flexibility when calibrating.

The CPG2300 Portable Digital Pressure Gauge can have one or two independent precision pressure sensors which can be displayed simultaneously. Channel A can be ordered with full scale ranges up to 6015 psi. Channel B can be ordered with ranges from 5 to 1000 psig or 7.5 to 1000 psia.

The user interface is through a monochrome 128 x 64 LCD, with white LED back light. A tactile membrane keypad makes navigation within the intuitive menu easy. Options to display range A and B, or range A or B and the analog measurement channel (mA), plus the ability to power a control loop make the CPG2300 ideal for field calibration of pressure and differential pressure transmitters. Built in functionality to display min/max peak pressure and rate per second per hour and per three hour plus a null function give the CPG2300 additional functionality for trouble shooting process pressure transmitters or monitoring barometric pressure.




Specifications

Model CPG2300

Specifications		
Accuracy ⁽¹⁾	FS	Ranges ≥ 1 psig 0.015% FS Ranges < 1 psig 0.030% FS
Calibration Stability (after warm up)		Better than 0.015% FS <1psig for 180 days with periodic re-zeroing.
Calibration interval		180 days
Calibration adjustment		Zero and Span may be reset without affecting linearity.
Channel A pressure ranges:		c
Channel B pressure ranges:		0... 5 up to 0...1000 psig 0...7.5 up to 0...1000 psia
Bidirectional pressure range:		-0.18 ... +0.18 up to -atm ... 6,000 psig
Pressure units		psi, in.Hg @ 0°C and 60°F, in.H ₂ O @ 4°C and 20°C, ft.H ₂ O @ 4°C, 20°C and 60°F, mTorr, inSW @ 0°C, ftSW @ 0°C, atm, bars, mbars, mmH ₂ O @ 4°C, cmH ₂ O @ 4°C, MH ₂ O @ 4°C, mmHg @ 0°C, cmHg @ 0°C, Torr, hPa, mPa, kPa, Pa, D/cm ² sq, g/cmsq, kg/cmsq, mSW @ 0°C, PSI, PSF, TSF, TSI, mHg @ 0°C, %FS. All seawater units are 3.5% salinity.
Resolution		5 digits on display; 6 digits over serial port
Overpressure limit		150% FS or greater, depending on range
Compensated temperature	°C	0 ... 50
Operating temp.	°C	0...50
Storage temp.	°C	-20 ... 70
Warm-up	min	< 1 to rated accuracy
Battery life	hr.	20
Recharge time	hr.	< 8
Reading rate	1/sec	~4.6
Response time	ms	<250 for FS pressure step
Communications		RS-232, 9600 baud, N, 8, 1
Case size	in.	T-Shaped, 8.6 H x 4.3 W x 1.6 D
Weight	lb.	Approximately 1.5
Media compatibility		Pressure port: Clean, dry, non-corrosive, non-combustible, non-oxidizing gases for all rated ranges. Ranges ≥ 5 psi: All other media compatible with aluminum, 316 stainless steel, brass, Buna N, Viton, sealant, silicone grease and RTV. Not designed for oxygen service. Reference port: Clean, dry, non-corrosive gases.
Fittings		1/4 inch FNPT pressure ports, nom. 1/16 inch hose barb for ref ports.
Power		+9 to +14.5 VDC, 830 mA max for battery recharge.
Options		Relief valves (mounted externally). 4-20 mA measurement with 24 VDC loop power source; current measurement accuracy: if span < 5psig, 0.03% R. If span ≥ 5 psig, 0.015% R
Display		Monochrome 128 x64 LCD with white LCD backlight.

1) It is defined by the total measurement uncertainty, which is expressed with the coverage factor (k=2) and includes the following factors: the intrinsic performance of the instrument, the measurement uncertainty of the reference instrument, long-term stability, influence of ambient conditions, drift and temperature effects over the compensated range during a periodic zero point adjustment.

Accessories

Accessories for CPC3050		Order code
Description		
Hand pump	 A hand-operated pump with a brass body, a black handle, and a coiled hose attached to a tripod stand.	--
Canvas case with belt clip	 A black canvas carrying case with a silver metal belt clip on the side.	--
Analog cables	 A bundle of three analog cables with different colored connectors (black, red, and black).	--

Specifications and dimensions given in this leaflet represent the state of engineering at the time of printing. Modifications may take place and materials specified may be replaced by others without prior notice.

All standard Mensor products are provided with a calibration certificate traceable to NIST. The calibration program at Mensor is accredited to both ISO/IEC 17025:2017 and Z540-1-1994 by A2LA. Mensor is certified to ISO9001:2015.



© 2024 WIKA Alexander Wiegand SE & Co. KG, all rights reserved.
The specifications given in this document represent the state of engineering at the time of publishing.
We reserve the right to make modifications to the specifications and materials.
In case of a different interpretation of the translated and the English data sheet, the English wording shall prevail.



Mensor LP
201 Barnes Drive
San Marcos, TX 78666 • USA
Tel. (+1) 512 3964200
Fax (+1) 512 3961820
E-Mail sales@mensor.com
www.mensor.com



Imported to Europe by:
WIKAL Alexander Wiegand SE & Co. KG
Alexander-Wiegand-Straße 30
63911 Klingenberg • Germany
Tel. +49 9372 132-0
Fax +49 9372 132-406
info@wika.de
www.wika.de

Imported to UK by:
WIKAL Instruments Ltd,
Unit 6 & 7 Goya Business Park,
The Moor Road, Sevenoaks
Kent, TN15 5GY